



Cars & trucks plugs ISO-compatible small hex plug

EX. K16R-U11 • K16PR-U11

Compatible with ISO standards * SKJ20DR-M11S with stainless steel gasket

14×L19×
○16
TOYOTA, and others

ISO TYPE

Cars & trucks plugs Small hex plug

EX. Q16R-U11 • Q16PR-U11

By reducing the hex size (16 mm), this plug is lighter in weight.

D14×L19×
○16
TOYOTA, and others

Cars & trucks plugs Extended shroud plug

EX. KJ20DR-M11 • KJ20DR-M11S

D14×L19×
○16
HONDA

Cars & trucks plugs Extended plug

EX. KJ20CR11 • KJ16CR-U11

5mm

KJ20CR11: no U-Groove
KJ20CR-U: with U-Groove

D14×L19×
○16
MAZDA, MITSUBISHI

Cars & trucks plugs Extended plug

EX. KJ20CR-L11

5mm

The tip of the ground electrode has a taper-cut, and the center electrode is made finer for improved ignitability.

D14×L19×
○16
HONDA

Cars & trucks plugs Double-electrode semi-surface plug

EX. W20ETR-S11

With this new supplementary gap, resistance to fouling is improved.

D14×L19×
○20.6
TOYOTA, DAIHATSU

Cars & trucks plugs Triple-electrode plug

EX. K22PB • W20EPB

Durability is improved with three ground electrodes.

D14×L19×
○16 (K22PB)
AUDI / VW / CITROEN / FIAT / MERCEDES-BENZ / RENAULT

Cars & trucks plugs 12 mm long-reach plug

EX. XU22HR9

D12×L26.5×
○16
DAIHATSU

Cars & trucks plugs 12 mm dia. plug

EX. XU22EPR-U

By reducing the hex size (16 mm), this plug may be used in light vehicles. Thread diameter is 12 mm.

D12×L19×
○16
SUZUKI / MITSUBISHI

Cars & trucks plugs 12 mm diameter long-reach plug with 14 mm hex size

EX. XE20HR-U9

D12×L26.5×
○14
RENAULT

Cars & trucks plugs Taper seat plug

EX. T16EPR-U

This plug may be installed only in non-Japanese cars and has no gasket.

D14×L17.5×
○16
GM, Ford

Motorcycle plugs Compact head plug

EX. W27EMR-C

Plug with compact insulator head

D14×L19×
○20.6
HONDA / SUZUKI

Motorcycle plugs 12 mm dia. shroud plug

EX. X24GP-U

19mm
3mm

D12×L (19 + 3)×
○18
HONDA

Motorcycle plugs 12 mm dia. × 19 mm plug

EX. X24EPR-U

D12×L19×
○18
HONDA / SUZUKI / YAMAHA

Motorcycle plugs 10 mm dia. plug with half-sized threads and stainless steel gasket

EX. U24FER9S

D10×L (6.3 + 12.7)×
○16
HONDA

6.3mm
12.7mm

Motorcycle plugs 10 mm dia. plug with half-sized threads

EX. U27FER9

With its wider spark gap of 0.9 mm compared to conventional plugs (0.6 to 0.7 mm), this plug has improved ignitability.

D10×L (6.3 + 12.7)×
○16
HONDA

6.3mm
12.7mm

Motorcycle plugs 10 mm dia. double-electrode plug

EX. U31ETR

With two ground electrodes, heat resistance is improved.

D10×L19×
○16
KAWASAKI / SUZUKI

Motorcycle plugs 10 mm dia. × 19 mm plug

EX. U27ESR-N

Increasing the projection length by 0.5 mm improves resistance to fouling.

D10×L19×
○16
YAMAHA / KAWASAKI / SUZUKI

Motorcycle plugs 10 mm dia. × 12.7 mm plug

EX. U20FSR-U

D10×L12.7×
○16
HONDA / YAMAHA / SUZUKI

Motorcycle plugs 8 mm dia. plug

EX. Y27FER-C

D8×L (6.3 + 12.7)×
○13
HONDA